# **APREJO**

# TOUCHES YOUR SENSES.

Whether with swing doors or folding doors: APREJO, the PALME Top-model, is very flexible and easily adaptable to any room situation. APREJO impresses with high-quality 8 mm tempered safety glass, selectable wall connections (Vario | Zero | Pro ) and high-quality design fittings made of metal die-cast.

- Standard at the highest quality level
- 25 year warantee
- up to 30 years spare part post-purchase warranty
- Simple installation
- Fast-delivery service: selected products can be delivered within 72 hours
- APREJO XXXpress: Selected products are produced within 9 days
- on request measurements and installations can be carried out by the PALME customer service
- Tested according to DIN EN 14428 CE.



**Glass:** 8 mm transparent tempered-safety glass

Doors:



Swing door



Folding door

The swing door opens inwards and outwards (Exception: 3-part round)
With folding doors the wall element opens 90° inwards and outwards. The door element is 180° foldable outwards.

**Comfort-features:** 



PALM.lift
Lifting/lowering mechanism



PALM.fix Magnetic catch



PALM.isi-clean Easy-care surface



PALM.pro (optional) Flush wall mounting



PALM.care (optional) Antibacterial profile



PALM.nano (optional) Nano-coating



PALM.free (optional)
Barrier-free



PALM.magic (optional) Ambient-lights

**Possible** 

wall connections:

Pro

The patented PALM.pro system profile makes a quick and simple wall mounting on the wall or flush-mount in the wall possible.

Vario Continuous wall attachment profile with 15 mm adjustment range.

Zero Selective wall mounting by two fittings for doors without fixed part.

3 soil solutions

are available:Barrier-free | discreet 4 mm baseboards | 15 mm high surge railAccessories (optional):Towel holder, glass shelf, Ambient-light, wall panel system

**Standard height:** 2.000 mm, Special height possible

**Possible widhts:** Swing door-widths up to 2.000 mm. Folding door-widths bis 1.400 mm

**Customised production:** Aprejo can be customised to the milimetre according to your individual request.

Awards:



Iconic Award










## **INSTALLATION SITUATION:**



# WALL PROFILES (from fixed wall elements):






Tip from the designer: For a perfect frameless design a flush mounting of the PRO-profile in the wall is possible. To that the profile has to be installed before the tiling work.

# WALL HINGE (for movable wall elements):






**HINGES:** 



















# **DESIGN GLASSES** (8 mm tempered safety glass):























## **PROFILE- UND HANDLE COLOURS:**











## **HANDLES**:







## **ACCESSORIES:**

















#### **RE-COVER WALL PANEL:**

Our Re-Cover wall covering makes completely new and simple ways of your wet areas' interior construction possible! In combination with discreet aluminium-end profiles it is possible to create a completely new atmosphere within no time.

#### **Product-information**

Aluminium-composite-wall covering with various decors and dimensions, combined with a decent aluminium end profile.

- Super easy to work with
- Abrasion-resistant, scratch-resistant, chemical-resistant, colour stable and
- Ideal for renovations: direct application on cleaned old tiles possible
- Fit accuracy at the joints
- Best cleaning comfort
- Optional also available with antibacterial PALM.care surface
- Standard at the highest level
- Easy mounting
- functional, economical and innovative solution
- Fast delivery service: Selected products can be delivered within 72 hours
- on request installations can be carried out by the PALME customer service
- Tested according to DIN EN 14428 CE.

#### Material, dimensions

- 6 mm Aluminium-composite-wall panels
- Format: 240 x 2.600 mm, 490 x 2.600 mm, 1.000 x 2.600 mm, 1.250 x 2.600 mm 1.500 x 2.600 mm,

Custom formats and customised productions are possible!



#### **Colours and decors**



Custom colours and photo scenes are possible!

Connection profile "PRO" 6 mm

#### **Profiles**

